




Fonrita
方瑞達電子


MOLDING POWER INDUCTORS

一體成型電感


Type: FDMC0518




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : FDMC (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHs Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:2000PCS.
- Square 5.7mm Max,Height 1.8mm Max.
- Powder iron core material.
- High current,low DCR,high efficiency.
- Widely use in DC-DC converter/Notebook/CPU/
Portable communications equipment/Camcorders/HDTV/car audio .

特長:

- 數量/卷:2000PCS.
- 方形5.7mm Max,高度1.8mm Max.
- 鐵合金材料.
- 大電流, 低直流電阻, 高效率.
- 廣泛應用於升降壓轉換器/筆記本電腦/電腦主板/
便攜式通訊設備/攝像機/高清電視/汽車音響.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	D.C.R. 直流電阻 Typ(m Ω)	Max(m Ω)	I sat(Typ.) 飽和電流(A)	I rms(Typ.) 溫升電流(A)
FDMC0518-R12	0.12	M	3.00	4.00	25.00	14.00
FDMC0518-R47	0.47	M	8.20	9.00	15.50	10.50
FDMC0518-R68	0.68	M	15.00	16.00	10.00	7.50
FDMC0518-1R0	1.0	M	15.00	17.00	9.00	8.00
FDMC0518-1R5	1.5	M	24.00	26.00	9.00	7.50
FDMC0518-2R2	2.2	M	33.50	35.00	6.50	5.00
FDMC0518-3R3	3.3	M	47.00	58.00	5.40	4.50
FDMC0518-4R7	4.7	M	73.00	85.00	4.00	3.50
FDMC0518-6R8	6.8	M	108.0	120.0	3.40	2.80
FDMC0518-100	10	M	134.5	155.0	3.00	2.50

Inductance Range/電感範圍:0.12~10 μH

Operating Temperature/工作溫度:-40°C ~ +125°C

Storage Temperature/儲存溫度:-40°C ~ +125°C

(1) Test frequency :100KHz/1.0V;


(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 30%,or temperature to rise by 40°C, whichever is smaller(At ambient reference temperature:25°C).

(1) 電感測試頻率:100KHz/1.0V;


(2) 最大容許電流定義:電感下降30%或溫度上升40°C時,取其小值作為最大容許電流(周圍環境溫度25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com