




Fonrita
方瑞達電子


MOLDING POWER INDUCTORS

一體成型電感


Type: FDMC0640




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : FDMC (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHs Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:1000PCS.
- Square 7.4mm Max,Height 4.0mm Max.
- Powder iron core material.
- High current,low DCR,high efficiency.
- Widely use in DC-DC converter/Notebook/CPU/
Portable communications equipment/Camcorders/HDTV/car audio .

特長:

- 數量/卷:1000PCS.
- 方形7.4mm Max,高度4.0mm Max.
- 鐵合金材料.
- 大電流, 低直流電阻, 高效率.
- 廣泛應用於升降壓轉換器/筆記本電腦/電腦主板/
便攜式通訊設備/攝像機/高清電視/汽車音響.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	D.C.R. 直流電阻		I sat(Typ.) 飽和電流(A)	I rms(Typ.) 溫升電流(A)
			Typ(m Ω)	Max(m Ω)		
FDMC0640-R15	0.15	M	0.90	1.00	30.0	28.0
FDMC0640-R22	0.22	M	1.00	1.50	28.0	26.0
FDMC0640-R33	0.33	M	2.90	3.60	25.0	24.0
FDMC0640-R47	0.47	M	4.00	4.50	21.0	20.0
FDMC0640-R68	0.68	M	4.00	4.80	19.0	18.0
FDMC0640-1R0	1.0	M	5.70	6.60	15.0	14.0
FDMC0640-1R5	1.5	M	8.00	10.00	12.5	12.4
FDMC0640-2R2	2.2	M	11.00	14.00	11.0	10.0
FDMC0640-3R3	3.3	M	18.50	20.0	10.0	8.5
FDMC0640-4R7	4.7	M	23.5	25.0	9.0	7.0
FDMC0640-6R8	6.8	M	40.0	45.0	6.5	5.5
FDMC0640-100	10	M	48.5	65.0	6.0	4.2
FDMC0640-150	15	M	75.0	95.0	4.5	3.7
FDMC0640-220	22	M	115.0	125.0	3.5	3.0
FDMC0640-330	33	M	200.0	250.0	2.7	2.0
FDMC0640-470	47	M	290.0	320.0	2.5	1.8

Inductance Range/電感範圍:0.15~47 μH

Operating Temperature/工作溫度:-40°C ~ +125°C

Storage Temperature/儲存溫度:-40°C ~ +125°C

(1) Test frequency :100KHz/1.0V;


(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 30%,or temperature to rise by 40°C, whichever is smaller(At ambient reference temperature:25°C).

(1) 電感測試頻率:100KHz/1.0V;


(2) 最大容許電流定義:電感下降30%或溫度上升40°C時,取其小值作為最大容許電流(周圍環境溫度25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com