




Fonrita
方瑞達電子


MOLDING POWER INDUCTORS

一體成型電感


Type: FDMC0650




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : FDMC (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHs Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:1000PCS.
- Square 7.4mm Max,Height 5.0mm Max.
- Powder iron core material.
- High current,low DCR,high efficiency.
- Widely use in DC-DC converter/Notebook/CPU/Portable communications equipment/Camcorders/HDTV/car audio .

特長:

- 數量/卷:1000PCS.
- 方形7.4mm Max,高度5.0mm Max.
- 鐵合金材料.
- 大電流, 低直流電阻, 高效率.
- 廣泛應用於升降壓轉換器/筆記本電腦/電腦主板/便攜式通訊設備/攝像機/高清電視/汽車音響.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	D.C.R. 直流電阻 Typ(m Ω)	Max(m Ω)	I sat(Typ.) 飽和電流(A)	I rms(Typ.) 溫升電流(A)
FDMC0650-R22	0.22	M	2.05	2.80	30.0	25.0
FDMC0650-R47	0.47	M	3.50	4.50	21.0	20.0
FDMC0650-R68	0.68	M	4.50	5.00	18.0	16.5
FDMC0650-1R0	1.0	M	5.50	6.50	15.0	12.0
FDMC0650-1R5	1.5	M	8.00	9.00	13.0	9.5
FDMC0650-2R2	2.2	M	10.00	12.50	12.0	8.0
FDMC0650-3R3	3.3	M	18.50	20.90	9.0	7.0
FDMC0650-4R7	4.7	M	22.0	25.0	8.0	6.5
FDMC0650-5R6	5.6	M	25.0	30.0	7.0	6.0
FDMC0650-6R8	6.8	M	35.0	41.0	7.0	5.5
FDMC0650-8R2	8.2	M	50.0	55.0	5.5	5.5
FDMC0650-100	10	M	50.0	55.0	6.0	4.5
FDMC0650-150	15	M	106.0	115.0	4.0	3.5
FDMC0650-220	22	M	130.0	145.0	3.5	2.5
FDMC0650-330	33	M	163.0	200.0	3.0	2.3
FDMC0650-470	47	M	230.0	260.0	2.5	2.0

Inductance Range/電感範圍:0.22~47 μH

Operating Temperature/工作溫度:-40°C ~ +125°C

Storage Temperature/儲存溫度:-40°C ~ +125°C

(1) Test frequency :100KHz/1.0V;


(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 30%,or temperature to rise by 40°C, whichever is smaller(At ambient reference temperature:25°C).

(1) 電感測試頻率:100KHz/1.0V;


(2) 最大容許電流定義:電感下降30%或溫度上升40°C時,取其小值作為最大容許電流(周圍環境溫度25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com